



# Adjustable Flow Handline Nozzles

## Features

- Construction of Chemlite or Brass
- 100 PSI standard operating pressure
- Removable pistol grip
- Durable chrome plated ball shut off
- Change flow without changing pattern
- Flush without shutting down
- Large rubber handle
- Multiple pattern detents for positive pattern positioning combination fog and straight stream
- Conforms to all aspect of NFPA 1964 Standards



## Suitable

- Refineries, Offshore Platforms, Chemical Plants, Storage Facilities, Fire Departments and more
- Suitable with water, In-Line Eductors, AFFF, AR-AFFF and Class "A" foam solutions

## Accessories

- Repair Kit
- Quick Clamp-On Foam Tube

Part No:	Inlet	GPM(lpm)	Length( cm)	Weight(kg)	Repair Kit	Material
MA10	1" NST	5-10-24-40 (19-38-91-152)	7" (18)	4 lbs.(1.8)	RK1000	CHEMLITE
MA10P*	1" NST	5-10-24-40	7" (18)	4 lbs. (1.8)	RK1000	CHEMLITE
MA15	1.5" NST	30-60-95-125 (114-227-360-473)	8"(20)	4.5 lbs. (2)	RK1001	CHEMLITE
MA15P*	1.5" NST	30-60-95-125	8"(20)	4.5 lbs. (2)	RK1001	CHEMLITE
MB15	1.5" NST	30-60-95-125	8.5"(22)	8.5 lbs. (4)	RK1001B	BRASS
MB15P*	1.5" NST	30-60-95-125	8.5"(22)	8.5 lbs. (4)	RK1001B	BRASS
MB15NPSH	1.5" NPSH	30-60-95-125	8.5" (22)	8.5 lbs. (4)	RK1001B	BRASS
MB15NPSHP*	1.5" NPSH	30-60-95-125	8.5" (22)	8.6 lbs. (4)	RK1001B	BRASS
MRA15	1.5" NST	30-60-95-125-150-200 (114-227-360-473-568-757)	10"(25)	7 lbs. (3)	RK1002	CHEMLITE
MRA15P*	1.5" NST	30-60-95-125-150-200	10" (25)	7 lbs. (3)	RK1002	CHEMLITE
MA25	2.5" NST	95-125-150-200-250 (360-473-568-757-946)	11"(28)	7 lbs. (3)	RK1002	CHEMLITE
MA25P*	2.5" NST	95-125-150-200-250	11" (28)	7.5 lbs. (3)	RK1002	CHEMLITE
MB25	2.5" NST	95-125-150-200-250	11" (28)	13.5 lbs. (6)	RK1002B	BRASS
MB25P*	2.5" NST	95-125-150-200-250	11" (28)	14 lbs. (6)	RK1002B	BRASS

\*Pistol Grip

**CHEM GUARD**  
 204 S. 6<sup>th</sup> Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606

[www.chemguard.com](http://www.chemguard.com)